

EMERGENCY SHUT DOWN OR SILENCING PANELS FOR MONITORED OR NON-MONITORED CUSTOMERS – AFTER HOURS

OTHER MANUFACTURERS

IF SIRENS ARE SOUNDING OR KEYPAD IS BEEPING – PRESS “#” ON KEYPAD AND THEN PUT IN YOUR 4 DIGIT SECURITY CODE

IF THIS DOES NOT SILENCE THE PROBLEM – SYSTEMS MUST BE POWERED DOWN BY DOING THE FOLLOWING AT THE MAIN CONTROL PANEL LOCATED IN CENTRAL CLOSET - FLASHLIGHT IS HIGHLY RECOMMENDED TO COMPLETE THIS PROCESS (BOTH (a) AND (b) MUST BE DONE)

STEP 1 DISCONNECT ONE LEAD OFF BATTERY (**MUST BE DONE BEFORE ANY OTHER PROCESS**)



STEP 2 LOCATE TRANSFORMER AT THE BOTTOM OF YOU CONNECTION CENTER OR IN THE ATTIC NEXT TO FURNACE THEN UNPLUG IT. (IF YOU CANNOT LOCATE THE TRANSFORMER YOU MUST PROCEED TO STEP 3)

STEP 3 LOCATE THE MAIN CONTROL PANEL IN CENTRAL CLOSET - FLASHLIGHT IS HIGHLY RECOMMENDED TO COMPLETE THIS PROCESS

STEP 4 LOCATE YOUR “AC TERMINALS FIRST (SAMPLE ABOVE) WIRE ON BOTH “AC” TERMINALS NEED TO BE DISCONNECTED – CUT ONE WIRE AT A TIME WITH SISSORS. (** SEE ABOVE TO LOCATE “AC” TERMINALS)

VIEW KEYPAD TO CONFIRM SYSTEM IS POWERED DOWN WITH NO LIGHTS ON KEYPAD

“NOTE”

THE ABOVE PROCESS IS BEING DONE AT YOUR OWN DESCRETION AND IT IS YOUR RESPONSIBILITY TO CONTACT OUR OFFICE THE FOLLOWING DAY TO SCHEDULE SERVICE

PLEASE BE AWARE THAT BY COMPLETEING STEP (2) YOU HAVE TOTALLY POWERED YOUR SYSTEM DOWN AND YOUR ALARM IN INACTIVE AT THAT POINT.

ALL OTHER MODELS AND MANUFACTURERS MAYBE RESET OR POWERED DOWN USING THE SAME PROCEDURE.